ENVIRONMENT CLEARANCE COMPLIANCE REPORT

October 2019 - March 2020

for

GRANITE BUILDING STONE QUARRY

(Minor Mineral)

Extent: 4.5180 Ha. (11.1639 Acres)

At

Re- Sy No. : 275/1A

Village : Tripangottur

Taluk : Thalassery

District : Kannur

State : Kerala,

'Granite Building Stone Quarry of Mr. Jovin George.' E.C.No:154/ECA/KNR/2018/DEIAA

Compliance Status of the General Conditions for Mining Projects Laid down by the State Environment Impact Assessment Authority, Kerala vide their Environment Clearance No.170/20178 dated: 19/05/2018.

SPECIFIC CONDITIONS

Sl.No	Condition	Status of Compliance
1	A Mines Manager shall be appointed to control, direct, manage and supervise Quarrying Operations as required under the Mines Act 1952.	A Mines manager is appointed to supervise Quarrying Operations.
2	Health and welfare measures for the persons employed shall be implemented.	Health and welfare measures for the employees are implemented.
3	Controlled blasting should be practiced, and blasting should be done only during day time. The mitigating measures for control of ground vibrations to arrest the fly rocks and boulders should be implemented.	All precautionary measures are adopted while blasting operations are carried out. I. No secondary blasting like Pop Shooting or Plaster Shooting are undertaken for breaking down large boulders, to avoid Air Blast and Fly Rocks. Only rock breakers will be used for breaking down bigger boulders. II. Additional precaution of controlled blasting with sand bags and wire mesh/blasting pads are used so that there are no fly rocks from the blast
4	Plantation shall be done which includes a green belt of adequate width around the Mining Lease area excluding the rocky area, along roads, overburden dumps and nonmineralized area by planting suitable native species in consultation with the local DFO/ Agriculture Department.	A green belt of a width of 7.5 mts has been made along the periphery of the Lease area by planting species in consultation
5.	The drains should be regularly desilted and maintained properly. Check dams and gully checks shall be constructed wherever required to arrest siltation. De siltation shall also be done every year before the onset of monsoon.	The drains will be constructed and maintained.
6	Fencing must be maintained properly all around the lease area.	The entire lease area is fenced and is well maintained.

7	The CSR should cover the felt needs of the locality with special emphasize for implementing ground water recharging techniques in and at the vicinity of the proposed site.	The CSR activities cover the needs of the locality with special emphasize for implementing ground water recharging techniques.
8	Appropriate sign boards should be displayed	Signboards have been displayed. (Photos are attached as Annexure-1)
9	The blasting time must be displayed and strictly adhered to.	Blasting time is displayed and is strictly followed (Annexure 1)
10	Dust suppression mechanism must be in place.	Water tankers with sprinklers are in use for dust suppression.
11	A separate small plot to be maintained in the premise to preserve rare and endemic species, if any, listed in the bio diversity assessment, etc.	No rare and endemic species is present in the lease area.
12	The PPV values must be less than 10 mm/sec.	PPV values are kept below 10 mm/sec.
13	The green belt shall be provided along the periphery.	Green belt of 7.5 mts width is provided along the periphery of the lease.
14	Where the height of the bench formed during earlier workings exceeds the maximum reach of the excavator engaged for work, such bench height shall be reduced from top to bottom.	Height of benches will be maintained as specified in the approved Mining Plan.
15	Loose or hanging rock or mineral boulder on the side wall shall be dressed down before engaging persons for work at the bottom of the bench.	Benches will be properly dressed by excavators and safety will be ensured before engaging employees at the bottom of the bench.
16	Permanent boundary pillars should be fixed by the proponent before commencing quarrying.	Permanent boundary pillars have been fixed. (Annexure 2)
17	No quarry blasting to be undertaken and sustained till warning time limit expires and/or when continuous 48 hours rainfall exceeds 8cms and blasting shall not be resumed until 24hours of rain free situation arises in the quarry locality based on the evaluation by the revenue officials.	Agreed.
18	All waste dumps and top soil dumps shall be properly stabilized using coir mats or bio regeneration. Proper drainage system shall be provided so that water is properly diverted away	Coir mats are used to cover waste dumps. Proper drainage system sare provided to divert the water away from the dump slopes.

	from the dumps slopes with no disturbance to the stability of the slopes.	
19	All dump slopes shall be sufficiently stabilized by using appropriate species mix of grass, creepers, shrubs and trees. This shall be done in consultation with the Forest department and local research institutes and experts I stabilization of mine dumps.	All dump slopes are stabilized as with grass, creepers, shrubs and trees done in consultation with the Forest department.
20	Garland drains of at least 2 mts width shall be provided all along 7.5 mts buffer zone to divert the water from entering the Quarry slopes. These drains shall be cleaned every year before the monsoon season	Garland drains of 2 mt width along the buffer zone will be constructed.
21	The water from the garland drainage shall be directed to the silt settling ponds. The clarified overflow from the silt settling ponds shall be directed to a Rain Water Harvesting (RWH) pond before releasing the clarified water to the natural water course.	Only clear natural water is let out into the natural water course.
22	A retaining wall of stone rubble with wire (2 mt) shall be constructed at the bottom of the slope of the Quarry lease to arrest any likely mesh of sufficient width and strength (not less than roll of boulders during heavy rainfall.	Retaining wall will be constructed.

GENERAL CONDITIONS OF HEALTH

Sl.No.	Conditions	Status of compliance
1	First Aid kit provided in the work site. It shall be periodically maintained properly. Some labourers shall be trained on First Aid.	First Aid kits are provided in the work site and key personnel is trained to render first aid in case of emergencies.
2	Wholesome drinking water should be provided.	Drinking water is provided.
3	Premises should be maintained as wet to suppress the dust.	Site premises is maintained wet to suppress the dust.
4	Sanitary type of latrines and urinals should be provided.	Latrines and urinals are provided.
5.	Resting place to be provided for workers	Resting place is provided to workers.
6	'No Smoking' board should be exhibited according to COTPA act.	'No Smoking' board is exhibited. (Annexure 1)
7	Work should not be done in night.	Work is done only during daytime.
8	Details of nearest hospital, shortest	Emergency contact numbers of Key

	route to hospital and contact no. etc. should be available	persons, Hospitals, police station, etc. is prominently displayed.
9	Approach roads should be maintained	Approach roads are well maintained.

GENERAL CONDITIONS

Sl.No	Condition	Compliance Status
1	Rainwater harvesting facility should be installed as per prevailing provisions of KMBR/KPBR, unless otherwise specified.	Rainwater harvesting facility will be installed.
2	Environment Monitoring Cell as agreed under the affidavit filed by the proponent should be formed and made functional.	Environmental Monitoring Cell has been formed and made functional.
3.	Suitable avenue trees should be planted along either side of the tarred road and open parking areas, if any, including approach roads and internal roads.	Avenue trees are planted along the sides of the tarred road.
4	Maximum Possible Solar Energy generation and utilization shall be ensured as an essential part of the Project.	Solar Energy generation and utilization shall be adopted.
5	Sprinklers shall be installed and used in the Project Site to contain dust emissions.	Water tankers with sprinklers are in use to control dust emission.
6	Eco-restoration, including the Mine Closure Plan shall be done at the own cost of the Project Proponent.	Agreed.
7	At least 10 per cent of total excavated Pit area should be retained as water storage area and the remaining area should be reclaimed with stacked dumping and overburden and planted with indigenous plant species that are eco-friendly, if no other specific condition on reclamation of the Pit is stipulated in the EC.	Agreed.
8	Corporate Social Responsibility (CSR) agreed upon by the Proponent should be implemented.	CSR activities are implemented as agreed.
9	The Lease area will be fenced off with barbed wires to a minimum height of 4 ft around, before starting of Mining. All the boundary indicators (boards, stores, markings, etc.) shall be protected at all times and shall be conspicuous.	Lease area is fenced off. Sign boards and boundary pillars have been erected at the site and protected.
10	Warning alarms indicating the time of Blasting (to be done at specific timings)	Warning alarms are installed and sirens are made before blasting for

	has to be arranged as per stipulations of the Explosives department.	indication.
11	Control measures on noise and vibrations prescribed by KSPCB should be implemented	Noise and vibrations are kept within KSPCB prescribed norms. I. Use of sharp drilling, delivery of compressed air at optimal pressure. II. Proper maintenance of compressor, drilling machine, jackhammers and tipper trucks. III. Regular monitoring of noise levels are being done within the core zone and the buffer zone of the mining lease area.
12	Quarrying activities should be limited to daytime as per KSPCB guidelines/specific conditions.	Quarrying activities limited to daytime.
13	Blasting should be done in a controlled manner as specified by the regulations of the Explosives department or any other agency.	Blasting is done in a controlled manner and is done technically as prescribed by the mining statutes. Only a small diameter drill holes of 33 mm diameter with 25mm cartridges slurry/ emulsion explosive are used for blasting, no large diameter holes are proposed for blasting. With optimum blast design, effective blasting techniques with delay detonators and low charges per delay, carte has been taken to limit the blast vibrations and the PPV value below 10mm per second.
14	A licensed person should supervise/control the Blasting Operations	Blasting supervision and control is done by a Mining Official having DGMS Certificate.
15	Access road to the quarry shall be tarred to contain dust emissions that may arise during transportation of materials.	Access road to the Quarry is tarred to control dust.
16	Overburden materials should be managed within the site and used for reclamation of Mine Pit as per Mine closure Plan/specific conditions	Overburden material is used for road making and as a filler along the Green Belt for plantation purpose.
17	Height of Benches should not exceed 5 M and width should not be less than 5 M, if there is no mention in the Mining Plan/specific conditions	Agreed.
18	Mats to reduce fly rock blast to a maximum of 10 PPV should be provided	Controlled blasting technique is adopted. PPV is kept to a minimum.

19	Maximum depth of Mining from general ground level at site shall not exceed 10 m	Agreed.
20	No Mining operations should be carried out at places having a slope greater than 45°	Agreed.
21	Acoustic enclosures should have been provided to reduce sound amplifications in addition to the provisions of green belt and hollow bricks envelop for crushers so that the noise level is kept within prescribed standards given by CPCB/KSPCB.	Crusher unit is not installed within Mining Lease.
22	The workers on the site should be provided with the required protective equipment such as ear muffs helmet, etc.	Requisite Personal Protective equipments (PPE's) is provided to all employees.
23	Garland drains with clarifiers to be provided in the lower slopes around the core area to channelize storm water.	Garland drains will be constructed
24	The transportation of minerals should be done in covered trucks to contain dust emissions.	All trucks transporting material are covered by firmly tied tarpaulin
25	The proponent should plant trees at least 5 times the loss that has been occurred while clearing the land for the project.	Plantation activities will be done with species collected in consultation with District Forest Office, Kannur.
26	Disposal of spent oil from diesel engines should be as specified under relevant Rules/Regulations.	Spent oil is reused as a lubricant for drilling.
27	Explosives should be stored in magazines in isolated place specified and approved by the Explosive Department.	Explosives is stored in a Licensed Explosives Magazine, which is approved by PESO. (Copy of the Explosive license is attached as Annexure-3)
28	A minimum buffer distance of 100 M from the boundary of the quarry to the nearest dwelling unit or other structures, not being any facility for mining shall be provided. (Read as 50m)	No dwellings are situated within 50m from the boundary of the quarry.
29	100 M buffer distance should be maintained from forest boundaries	Mining area is not located near any forest areas.
30	Consent from Kerala State Pollution Control Board under Water and Air Act(s) should be obtained before initiating mining activity.	Consent from KSPCB under Air and Water Act(s) is obtained.

31	All other statutory clearances should be obtained, as applicable, by project proponents from the respective competitive authorities including that for blasting and storage of explosives.	All required statutory clearances obtained. The DGMS permission is under process.
32	In the case of any change(s) in the scope of the Project, extent, quantity, process of mining technology involved or in any way affecting the environment parameters/impacts as assessed, based on which only the EC is issued, the project would require a fresh appraisal by this Authority, for which the proponent shall apply and get the approval of this Authority.	There is no change in the scope of mining.
33	The Authority reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the Environmental Clearance under provisions of the Environment (Protection) Act,1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.	Agreed.

34	The stipulations by the Statutory Authorities under different Acts and Notifications should be complied with including the provisions of the Water (Prevention and control of Pollution) Act,1974, the Air (Prevention and control of Pollution) Act1981, the Environment (Protection) Act,1986, the Public Liability (Insurance) Act,1991 and EIA Notification,2006	Agreed.
35	The project proponent should advertise in at least 2 newspapers widely circulated in the region, one of which(both the advertisement and the newspaper) shall be in the vernacular language informing that the Project has been accorded Environment Clearance and the copies of the Clearance letters are available with the State Environment Impact Assessment Authority (SEIAA) office and may also be seen on the website of the Authority at www.seiaakerala.org . The advertisement	Advertisements informing EC accordance to the Project is done in 2 no's newspapers and submitted in earlier report.

	should be made within 10 days from the date of receipt of the clearance letter and a copy of the same signed in all the pages should be forwarded to the Office of this Authority as confirmation	
.36	A copy of the clearance letter shall be sent by the proponent to the concerned Gram Panchayat/District Panchayat/Municipality/Corporation/Urban local Body and also to the Local NGO, if any from whom suggestions/representations, if any were received while processing the proposal. The Environmental Clearance shall also be put on the website of the company by the proponent.	A copy of the Clearance is submitted to panchayat. (Enclosed as Annexure-4)
37	The proponent shall submit half yearly reports on the status of compliance of the stipulated EC conditions including results of monitored data (both in hard copies as well as by e-mail) and upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the respective Regional office of the MOEF, Govt. of India and also to the State Environment Impact Assessment Authority (SEIAA) office	Half yearly reports are submitted as stipulated
38	The details of Environment Clearance should be prominently displayed in a metallic board of 3 ft x 3 ft with green background and yellow letters of Times Roman font of size not less than 40. Sign board with extent of Lease area and boundaries shall be depicted at the entrance of the quarry, visible to the public	Details of Environmental Clearances are prominently displayed at the entrance to the Mine. (photo of the sign board is Attached as Annexure-1)
39	The proponent should provide notarized affidavit (indicating the number and date of Environmental Clearance proceedings) that all the conditions stipulated in the EC shall be scrupulously followed.	Provided.
40	No change in mining technology and scope of working should be made without prior approval of the SEIAA. No further expansion or modifications in the mine shall be carried out without prior approval of the SEIAA, as applicable.	Prior approval from the SEIAA will be sought in case of change of mining technology.
41	The Project proponent shall ensure that no	No natural water course is

	natural water course and/or water resources shall be obstructed due to any mining operations. Necessary safeguard measures to protect the first order streams, if any, originating from the mine lease shall be taken.	obstructed. Necessary safeguard measures will be taken to protect first order streams if originating from the mining lease in the future.
42	Monitoring of Ambient Air Quality to be carried out based on the Notification 2009, as amended from time to time by the Central Pollution Control Board. Water sprinkling should be increased at places loading and unloading points & transfer point to reduce fugitive emissions.	Monitoring of Ambient Air Quality will be carried out. Water sprinkling will be done at places of loading and unloading & transfer point to reduce fugitive emissions. (Monitoring Photos & Report are attached as Annexure 5 & 6)
43	The top soil, if any, shall be temporarily be stored at earmarked site(s) only for the topsoil shall be used for land reclamation and plantation. The Over burden (OB) generated during the mining operations shall be stacked at earmarked dump site(s) only. The maximum height of the dumps shall not exceed 8 m and the width 20 m and overall slope of the dumps shall be maintained to 45°. The OB dumps should be scientifically vegetated with suitable native species to prevent erosion and surface run off. In critical areas, use of geo-textiles shall be undertaken for stabilization of the dump. The entire excavated area should continue until the vegetation becomes self-sustaining	Available top soil will be used at the Green belt for plantation. OB generated is used for plantation purposes along the Green/Safety zone.
44	Catch drains and siltation ponds of appropriate size shall be constructed around the mine working, mineral and OB dumps to prevent run off of water and flow of sediments directly into the river and other water bodies. The water so collected should be utilized for watering the mine area, roads, green belt development, etc. The drains shall be regularly de silted particularly after monsoons and maintained properly	Catch drains will be made along the periphery of the mining lease.
45	Effective safeguard measures such as regular water sprinkling shall be carried out in critical areas prone to air pollution and having high levels of PM10 and PM2.5 such as haul road, loading and unloading points and transfer points-it shall be ensured that the Ambient Air Quality parameters conform to the norms prescribed by the Central Pollution Control Board in this regard.	Regular water sprinkling is done on haul roads with water tankers at haul roads, loading, unloading points and transfer points.

46	Fugitive dust emissions from all sources should be controlled regularly. Water spraying arrangements on haul roads, loading and unloading and transfer points should be provided and properly maintained.	Fugitive dust emissions are controlled by spraying on haul roads, loading and unloading and transfer points
47	Measures should be taken for control of noise levels below 85 dB(A) in the work environment.	Adequate measures for noise control is adopted.
48	A separate environmental management cell with suitable qualified personnel should be set up under the control of a senior executive, who will report directly to the head of the Organization.	An Environment Management Cell is set up under the control of the Mines Manager.
49	The funds earmarked for environment protection measures and CSR activities should be kept in a separate account and should not be diverted for other purpose. Year wise expenditure should be reported to the State Environment Impact Assessment Authority (SEIAA) office.	The funds earmarked for environment protection measures and CSR activities are be kept in a separate account and is not diverted for other purposes.
50	The Regional Office of MOEF and CC located in Bangalore shall monitor compliance of the stipulated conditions. The Project authorities should extend full cooperation to the Officer(s) if the Regional Office by furnishing the requisite data/information/monitoring reports.	We will extend full cooperation to any officer(s) from the Regional Office during his/their visit. All available data will be provided.
51	Any appeal against the Environment Clearance shall lie with the National Green Tribunal, if preferred, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010	Agreed.
52	Concealing the factual data or submission of false/fabricated data and failure to comply with any of the conditions mentioned above may result in withdrawal of this clearance and attract action under provisions of the Environment (Protection) Act, 1986.	Factual and true data will be submitted.
53	The SEIAA may revoke or suspend the order for non-implementation of any of the specific or this implementation of any of the above conditions is not satisfactory. The SEIAA reserves the right to alter/modify the above conditions or stipulate any further condition in the interest of the environment protection	Agreed.
54	The above conditions shall prevail not withstanding anything to the contrary,	Agreed.

	inconsistent or simplified, contained in any other permit, license on consent given by any other authority for the same project.	
55	The order is valid for a period of 5 years of the expiry date of Mine lease period issued by the Government of Kerala, whichever is earlier	Agreed.
56	The Environment Clearance will be subject to the final order of the courts in any pending litigation related to the land or the project, in any court of law.	Agreed.
57	The Mining operations shall be restricted to above ground water table and it should not intersect ground water table.	Mining operations will be restricted to above ground water table and due care will be taken so as not to intersect ground water.
58	All vehicles used for transportation and within the mines shall have 'PUC' certificate from authorized pollution checking center. Washing of all vehicles shall be inside the Lease area	Will ensure that all transportation vehicles have PUC issued by an authorized Pollution checking center.
59	Project proponent should obtain necessary prior permission of the competent authorities for drawl of necessary quantity of surface and ground water for the project.	Agreed.
60	Regular monitoring of flow rates and water quality upstream and downstream of the springs and perennial nallahs flowing in and around the mine lease area shall be carried out and reported in the six-monthly reports	No perennial nallah flows through the lease or exist around the Mine Lease.
61	Occupational health surveillance program of the workers should be undertaken periodically to observe any contractions due to exposure to dust and take corrective measures, if needed.	Occupational health surveillance will be undertaken.

For 'Granite Building Stone of Mr.Jovin George'

(Mr.Jovin George)

Owner Date: 24.07.2020

Annexure 1









Annexure 2





भारत सरकार | Government of India

वाणिज्य और उद्योग मंत्रालय | Ministry of Commerce & Industry

पेट्रोलियम तथा विस्फोटक सरक्षा संगठन (पेसो) | Petroleum & Explosives Safety Organisation (PESO)

पूर्व नाम- विस्फोटक विभाग | Formerly- Department of Explosives केन्द्रीय भवन, ब्लाक सी-2, तीसरी मंजिल | Kendriya Bhavan, Block C-2, 3rd Floor

CSEZ पी.ओ कक्कानाड कोच्ची | CSEZ PO Kakkanad Dist. Ernakulam Ernakulam 682037 फोन (Phone):- 2427286 | फैक्स (Fax):- 2427276 ई-मेल Email: dvcccernakulam@explosives.gov.in

संख्या (No.): E/SE/KL/22/18(E85231)

दिनांक (Date): 07/02/2019

सेवा में । То. JOVEN GEORGE.

Madathinamattathil House, Palisseri, Thalassery P.O., Thalassery, Kannur, Town/Village - Palisseri

- 8 FEB 2019

विषय .

District-KANNUR, State-Kerala, Pincode - 670101 Survey No.275/1A. ग्राम Tripangottur. जिला KANNUR, राज्य Kerala में विस्फोटक के मैगजीन में उपयोग के लिए कब्जा हेत

विस्फोटक नियम. 2008 के अंतर्गत LE-3 में जारी अनुजिस सं E/SE/KL/22/18(E85231) के नवीनीकरण संदर्भ में। Possession for Use of of Explosives from magazine situated at Survey No.:275/1A, Tripangottur, Dist. KANNUR, Kerala -Licence

Subject: No.: E/SE/KL/22/18(E85231) granted in Form LE-3 of Explosives Rules, 2008 - Renewal regarding

महोदय | Sir.

आपका उपर्युक्त विषय पर पत्र संख्या Nil दिलांक 30/01/2019 का संदर्भ ग्रहण करें। विस्फोटक नियम, 2008 के अंतर्गत प्ररूप LE-3 में जारी अनुजिस दिलांक

31/3/2024 तक नवीनीकत कर इस पत्र के साथ भेजी जा रही है। Reference to your letter No.: Nil dated: 30/01/2019, the subject licence duly renewed upto 31/3/2024 and issued in Form LE-3 of Explosives Rules, 2008 is forwarded herewith.

अनुज्ञप्ति के आगामी नवीकरण हेत् कृपया निम्नलिखित दस्तावेज दिनांक 31/03/2024 से पहले इस कार्यालय को भेजे जाएं.

For further renewal of licence, please submit the following documents so as to reach this office on or before 31/3/2024.

• प्ररूप आरई-। में विधिवत पूर्ण एवं हस्ताक्षरित आवेदन। Application in Form RE-1 duly filled in and signed.

एक से पाँच वर्ष के अनुजिस शुल्क का बैंक ड्राफ्ट। बैंक ड्राफ्ट किसी भी राष्ट्रीयकृत बैंक के नाम आहरित, संयुक्त मुख्य विस्फोटक नियंत्रक, चेल्नई के पक्ष में चेन्नई में देय हों। Licence fees for one to five years in the form of demand draft drawn on any Nationalized Bank in favour of Jt. Chief Controller of Explosives,

Chennai payable at Chennai. • अनुमोदित प्लान के साथ मूल अनुज्ञित।

Original licence with approved plan. कपया इस संबंध में विस्फोटक नियम, 2008 के नियम 112 का भी संदर्भ ग्रहण करें। In this connection, please also refer to Rule 112 of Explosives Rules, 2008.

• विस्फोटकों के क्रय हेत् आरई-11 में मांगपत्र (इंडेंट) आपूर्तिकर्ता को दिया जाए और उसी की एक प्रति इस कार्यालय को भेजी जाएं (आतिशबाजी गोदाम के लिए लागू नहीं)।

Indent for purchase of explosives shall be placed in RE-11 with the supplier and copy of the same shall be sent to this office. (Not applicable for fireworks store house) कृपया विस्फोटकों की त्रैमासीक विवरणी हर तिमाही के अंत में आरई-7 में प्रस्तूत की जाएं । विवरणी इस कार्यालय के कार्यालय में आगामी

तिमाही के 10 तारीख से पहले पहुंच जानी चाहिए (आतिशबाजी गोदाम के लिए लागू नहीं) I Please submit quarterly returns of explosives in RE-7 at the end of every quarter so as to reach this office by 10th of the succeeding quarter. (Not applicable for fireworks store house)

• सभी ब्लास्टिंग आपरेशन एक सक्षम द्वारा की जाएगी जो उपरोक्त नियमों के तहत एक वैध शॉट फायर प्रमाणपत्र धारक हो। हालांकि, खान अधिनियम 1952 के अधीन आने वाले खानों में ब्लास्टिंग आपरेशन करने वाले ब्लास्टर की योग्यता उसी अधिनियम से निर्धारित हो। All blasting operations shall be carried out by a competent person holding a valid shot firer's permit granted under above rules. However, blasting operations in mines coming under the purview of the Mines Act 1952, the blaster shall have qualifications prescribed in the regulations framed under the said Act.

आपके खाते में रुपए 700/- की राशि शेष हैं जो इस संदर्भ को उद्धत करते हुए भविष्य के संव्यवहार में समायोजित की जा सकती है। An amount of Rs. 700/- balance is in your credit, which may be utilized for future transaction by quoting this reference.

भवदीय | Your's faithfully

(आर.वेणुगोपाल | Dr. R.Venugopal)

5प मुख्य विस्फोटक नियंत्रक | Deputy Chief Controller of Explosives

प्रतिनिपि प्रेषित | Copy Forwarded to:

उप मुख्य होत्या Ernakulam त्रक Deputy Chief Controller of Explosives एरणाकलम Ernakulam

1. जिला मजिस्ट्रेट (District Magistrate), KANNUR (Kerala)- सूचना के लिए (for information.)

उप मुख्य विस्फोटक नियंत्रक | Deputy Chief Controller of Explosives कोच्ची | Ernakulam

(अधिक जानकारी जैसे आवेदन की स्थिति, शुल्क आदि के लिए हमारी वेबसाइट http://peso.gov.in देखें

अनुज्ञित प्ररूप एल. ई.-3 | LICENCE FORM LE-3

(विस्फोटक नियम, 2008 की अनुसूची 4 के भाग 1 के अनुच्छेद 3(क) से (घ) देखिए।) (See article 3(a) to (d) of Part 1 of Schedule IV of Explosives Rules. 2008)

वयोग के लिए एक समय पर वर्ग 1,2,3,4,5 या वर्ग 7 के विस्फोटक या किसी मैगजीन में वर्ग 6 के विस्फोटक रखने के लिए अनज्ञि

Licence to possess: (c) for use, explosives of class 1, 2,3,4,5,6 or 7 in a magazine

अनुज्ञास सं. (Licence No.) : E/SE/KL/22/18(E85231) वार्षिक फीस रुपए (Annual Fee Rs): 2400/-

1. Licence is hereby granted to

JOVIN GEORGE (अधिभोगी / Occupier : JOVIN GEORGE), Madathinamattathil House, Palisseri, Thalassery P.O., Thalassery, Kannur, Town/Village - Palisseri, District-KANNUR, State-Kerala, Pincode -

को अनुज्ञप्ति अनुदत्त की जाती है।

2. अनुज्ञिभधारी की प्रास्थिति | Status of licensee : Individual

3. अनुज्ञप्ति निम्नलिखित प्रयोजनों के लिए विधिमान्य Licence is valid only for the following purpose.

possess for use of Nitrate Mixture, Safety Fuse, Electric and/or Ordinary Detonators, के उपयोग के लिए

4. अनुराति विस्फोटकों के निम्नलिखित किस्मों, प्रकार और मात्रा के लिए विधिमान्य है।

Licence is valid for the following kinds and quantity of explosives: -- (क) (a)

क्र Sr. No.	नाम और विवरण Name and Description	वर्ग और प्रभाग Class & Division	उप-प्रभाग Sub-division	मात्रा किसी एक समय में Quantity at any one time
1	Nitrate Mixture	2.0	0	125 Kg.
2.	Safety Fuse	6.1	0	2000 Mtrs
3.	Electric and/or Ordinary Detonators	6,3	0	3000 Nos.

(ख) किसी एक कलैंडर मास में खरीदे जाने वाले विस्फोटक की मात्रा [अन्च्छेद 3(ख) और (ग) के अधीन अनुज्ञित के लिए।

25 times as above.

(b) Quantity of explosives to be purchased in a calendar month[applicable for licence under article 3(b) and (c)1:

5. निम्नलिखित रेखाचित्र (रेखाचित्रों) से अन्जप्त परिसर की पृष्टि होती

जिला (District)

दरभाष (Phone)

रेखाचित्र क्र. (Drawing No.) E/SE/KL/22/18(E85231) दिनांक (Dated) 05/03/2015

The licensed premises shall conform to the following drawing(s):

6. अनुज्ञप्ति परिसर निम्नलिखित पते पर स्थित हैं। The licensed premises are situated at following address:

Survey No. 275/1A , ग्राम (Town/Village) : Tripangottur KANNUR

9447485245

राज्य (State) ई. मेल (E-Mail)

पुलिस थाना (Police Station) : Kolavalloon पिनकोड (Pincode) Kerala फैक्स (Fax)

670693

अनुज्ञि परिसर में निम्नलिखित स्विधाएं अंतर्विष्ट हैं।

: Two cemented magazines

The licensed premises consist of following facilities.

8. अनुजित समय – समय पर यथासंशोधित विस्फोटक अधिनियम, 1884 और उनके अधीन विरचित विस्फोटक नियम, 2004 के उपबंधों, शर्तों और अतिरिक्त शर्तों और निम्नलिखित उपाबध्दों के अधीन रहते हुए अनुदत्त की जाती है। The licence is granted subject to the provision of Explosives Act 1884 as amended from time to time and the Explosives Rules, 2008 framed there under and the conditions, additional conditions and the following Annexures.

 उपर्युक्त क्रम सं. 5 में यथा कथित रेखाचित्र (स्थान, सिन्निर्माण संबंधी और अन्य विवरण दर्शित करते हुए)। Drawings (showing site, constructional and other details) as stated in serial No. 5 above.

2. अनुजिस प्राधिकारी व्दाररा हस्ता.क्षरित इस अनुजिस की शर्ते और अतिरिक्ति शर्ते। Conditions and Additional Conditions of this licence signed by the licensing authority.

3. द्री प्ररूप DE-2 | Distance Form DE-2.

9.

यह अनुज्ञित तारीख 31 मार्च 2019 तक विधिमान्य रहेगी। This licence shall remain valid till 31st day of March यह अनुज्ञित, अधिनियम या उसके अधीन विरचित नियमों या अनुसूची V के भाग 4 के प्रति निर्दिष्ट सेट-VII के अधीव तथा उपवर्णित इस अनुजाित की शर्तों का अधिक्रमण करने या यदि अनुजात परिसर योजना या उससे संलग्न उपबंध मे दर्शित विवरण के अनुरूप नहीं पाए जाने पर निलंबित या प्रतिसंहत की जा सकती है, जहां वह लागू हो। This licence is liable to be suspended or revoked for any violation of the Act or Rules framed there under or the conditions of this licence as set forth under Set VIII, wherever applicable, referred to in Part 4 of Schedule V or if the licensed premises are not found conforming to the description shown in the plans and Annexure attached hereto.

तारीख | The Date - 05/03/2015

उप मुख्य विस्फोटक नियंत्रक | Dy. Chief Controller of Explosive

Ernakulan

Amendments :

- Amendment of Quantity of Explosives/Monthly Purchase Limit dated: 15/03/2016
- Amendment of Quantity of Explosives/Monthly Purchase Limit dated: 15/01/2018
- Amendment of Quantity of Explosives/Monthly Purchase Limit dated: 08/08/2018 Amendment of Quantity of Explosives/Monthly Purchase Limit dated: 23/10/2018
- Transfers :

Change in Licensee Name/Address/Status dated: 10/07/2017

नवीनीकरण के पृष्ठांकन के लिए स्थान Space for Endorsement of Renewal

नवीकरण की तारीख Date of Renewal	समाप्ति की तारीख Date of Expiry	अनुनापन प्राधिकारी के हस्ताक्षर और स्टाम्प Signature of licensing authority and stamp
07/02/2019	31/03/2024	Dy. Chief Controller of Explosives, Ernakulam
		Deputy Chief Controller of Explosives

कानूनी चेतावनी : विस्फोटकों को गलत ढंग से चलाने या उनका दुरूपयोग विधि के अधीन गंभीर दांडिक अपराध होगा। Statutory Warning: Mishandling and misuse of explosives shall constitute serious criminal offence under the law.



തൃപ്രങ്ങോട്ടർ ഗ്രാമപഞ്ചായത്തില് നിന്നും 1994 ലെ കേരള പഞ്ചായത്ത് രാജ് ആക്ട് (1994ലെ 13) 232,233,234,254 എന്നീ വകപ്പകളം അതേ തുടർന്നുള്ള ചട്ടങ്ങളം അനസരിച്ച് നൽകുന്ന

ഡി & ഒ ലൈസൻസ്

ലൈസൻസിയുടെ പേരും മേൽവിലാസവും	 ജോവിൻ ജോർജ്ജ് മടത്തിനാമറ്റത്തിൽ,
	പാലിശ്ശേരി, തലശ്ശേരി (പി.ഒ) 670101
സ്ഥാപനത്തിൻറെ പേരും	റി.സ 275/1എ
സ്ഥലനാമവും	നരിക്കോട്ട് മല
.! ലൈസൻസ് നൽകിയിട്ടുള്ള	കരിങ്കൽഖനനം നടത്തുന്നതിന്
പ്രവർത്തനങ്ങള്	
കെട്ടിട നമ്പരും വാർഡ്	റി.സ 275/1എ
നമ്പരം	നരിക്കോട്ട് മല
ലൈസൻസ് കാലയളവ്	01/04/2019 മുതല് 31/03/2020 വരെ
ഈടാക്കിയ ലൈസൻസ് ഫീസ്	5000/-
1	ലസൻസ് അനുവദിക്കുന്നതിനായി
1	യ നിരാക്ഷേപ പത്രങ്ങളുടെ വിശദാംശങ്ങൾ

- 1. ഡിസ്ക്കിക് എൻവയോൺമെൻറല് ഇംപാക്ക് അസസ് മെൻറ് അതോറിറ്റി യുടെ 22/05/2017തീയ്യതിയിലെ 01/KNR/2017/DEIA നമ്പർ അനുമതി, ഡിസ്കിക്ക് എൻവയോൺമെൻറല് ഇംപാക്ക് അസസ് മെൻറ് അതോറിറി യുടെ 19/05/2018 തീയ്യതിയിലെ 154/ECA/KNR/2018/DEIAA നമ്പർ അനമതി.
- 2. കേരള സംസ്ഥാന മലിനീകരണ നിയന്ത്രണ ബോർഡിൻറെ 19/06/2018 ലെ PCB/KNR/ICO-R/360/2017 23/05/2017 ലെ PCB/KNR/ICO-R/360/2017 നമ്പര് അനമതി.
- 3. മൈനിംഗ് ആൻറ് ജിയോളജി ഡിപ്പാർട്ട്മെൻറില് നിന്നും 16/08/2018 തിയ്യതിയിലെ No.367/2018-

19/3326/M3/2018/DMG നമ്പര് നടപടിക്രമം , 04/10/2017 NO.409/2017-18/8825/M3/2016/DMG നമ്പർ നടപടിക്രമം.

- ചിഫ് കൺടോളർഓഫ് ഏക്സ്ലോസിവ് അധ്കൃതരുടെ അനുമതി.
- 5. തൃപ്രങ്ങോട്ടർ വില്ലേജ് ഓഫീസറുടെ 05/02/2019 തിയ്യതിയിലെ 37709654,37785764 നമ്പര് കൈവശാവകാശ സർട്ടിഫിക്കറ്റുകൾ
- തൃപ്രങ്ങോട്ടർ പ്രാഥമിക ആരോഗൃകേന്ദ്രം ഹെൽത്ത് ഇൻസെക്ലറ്റടെ ശ്രചിത്വ സർട്ടിഫിക്കറ്
- 7. ക്വാറി നടത്താനുദേശിക്കുന്ന സർവ്വേ മാന്റ്രാ^{t Gram}a
- പാറപ്പൊട്ടിക്കുന്ന ആളടെ വൈദഗ്ധ്യം നാംബുസ്ലിച്ചള്ള സർട്ടിഫിക്കറ്റ്
- സ്ഥല ഉടമസ്ഥൻറെ സമ്മതപത്രം



KERALA STATE POLLUTION CONTROL BOARD

FILE NO.: PCB/KNR/ICE/1915/2014

Date of issue :2018-06-19

CONSENT VARIATION ORDER

Consent No: PCB/KNR/ICO-R/360/2017

Ref: 1. Consent No: PCB/KNR/ICO-R/360/2017 Dated 23/05/2017.

The 'Integrated Consent to Operate' issued as per reference above to M/s QUARRY OWNED BY JOVIN GEORGE, PATHIKAL, POYILOOR.P.O., KANNUR DT - 670693 is hereby modified & issued to M/s QUARRY OWNED BY JOVIN GEORGE, PATHIKAL, POYILOOR.P.O., KANNUR DT - 670693 The consent(s)/ variation order(s) cited under reference are integral part of this consent variation order and this order is subject to the conditions stipulated therein and the following modifications/ additions.

I GENERAL

S.No.	Items	Description
1	1.16 ACTIVITY	Granite quarrying of 4.5180 Ha in RS 275/1A of Thrippangottur Village of Thalassery Thaluk
2	1.1 VALIDITY	30/04/2023
3	1.10 CATEGORY	RED
4	1.12 ANNUAL FEE	25000/-
5	1.13 TOTAL FEE REMITTED	125000/-

II. CONDITIONS

2.2 Application for renewal of consent shall be submitted before 28/02/2023.

All other conditions of the Integrated Consent to Operate issued as per reference above remain unchanged.

DATE :19/06/2018 SIGNATURE & SEAL OF ISSUING AUTHORITY ENVIRONMENTAL ENGINEER



To JOVIN GEORGE, MADATHINAMATTATHIL HOUSE, PALISERI, THALASSERY.P.O., THALASSERY, KANNUR DT - 670101

- 1. This digitally signed document is legally valid as per the Information Technology Act 2000
- 2. For verifying this document please go to krocmms.nic.in and search using date of issue/name of the unit/Application Number in "Consent Granted Applications" link in the home page of the Board's Online Consent Management and Monitoring System.

Annexure 5











(Consulting Engineers, Mine designers, Geologist & Surveyors) 3 nd Main Road, Basayeswara Badayane

HOSPET - 583201. Dist. Bellary (Karnstaks) Ph +01 8394 229433 & 295018 gens hot@vahoo.com. Website www.globalmining in

> GEMS-LD/TF/11/01 Date: 09.03.2020

Analysis Report of Ambient Air Quality Monitoring

'Granite Building Stone Quarry of

Shri. Jovin George'

Name of the Customer/Address

: Extent: 4.5180 Ha, (11,1639Acres)

Sv. Nos: 275/1A, Tripangottur Village,

2 Sample Description

3 Sample Collected By

4 Duration of the Monitoring

5 Location of Monitoring

Report No

Thalassery Taluk, Kannur District, Kerala State.

Ambient Air Quality Monitoring

GLOBAL Environment & Mining Services

: 24 Hour of Sampling : (A1) Core zone

: ULR-TC532320000000101F

Result

Si No.	Date		P	'arameters in μg/m	n ³	
		PM_{10}	PM2.5	SO ₂	NO ₂	Lead in PM
1	07.03.2020	50.8	21.6	12.3	11.5	BDL
NAA	AQ Standards 2009	100	60	80	80	1.0

PM10 - IS 5182 (Part 23): 2006 (RA 2017)

PM2.5 - USEPA 2001

SO2 - IS 5182 (Part 2): 2001 (RA 2017) BDL (<3.0)

- IS 5182 (Part 6): 2006 (RA 2017) BDL ((<5.0) NO2 - IS 5182 (Part 22): 2004 (RA 2014) Lead

BDI. - Below Detectable Limit.

Analyzed By J.M. Thippeswamy Chemist

K. Ramakashnosenay Technica Manager

Note:

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles 7 Days and ILC samples from the date of issue of Month test certificate unless etherwise
- This report is not to be reproduced whelly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.
 Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only

Approved by NABL & Recognized by Ministry of Environment, Forest and Climate Change for Laboratory

Recognized by Government of Kannataka, Maharashira, Goa for DGPS survey





4

5

GLOBAL Environment & Mining Services

(Consulting Engineers, Mine designers, Geologist & Surveyors) 3 Main Road, Basaveswara Badavane, HOSPET - 583201, Dist., Bellary (Kamataka)

Ph : +91 8394 229433 & 295018

e-mail gems hpt@yalioo.com. Website : www.globalinining.in

> GEMS-LD/TF/11/01 Date: 09.03.2020

Analysis Report of Ambient Air Quality Monitoring

'Granite Building Stone Ouarry of

Shri. Jovin George'

Name of the Customer/Address : Extent: 4.5180 Ha. (11.1639Acres)

Sv. Nos: 275/1A, Tripangottur Village,

Thalassery Taluk, Kannur District, Kerala State.

Sample Description 2 : Ambient Air Quality Monitoring 3 Sample Collected By

GLOBAL Environment & Mining Services

: 24 Hour of Sampling

Location of Monitoring (A2) Buffer Zone Report No : ULR-TC532320000000102F

Result

Si No.	Date	Date	Pa	rameters in μg/r	n ³	
		PM_{10}	PM _{2.5}	SO ₂	NO ₂	Lead in PM
1	06.03.2020	41.8	16.2	13.1	12.3	BDL
NAA	AQ Standards 2009	100	60	80	80	1.0

PM10 - IS 5182 (Part 23): 2006 (RA 2017)

PM2.5 - USEPA 2001

Duration of the Monitoring

SO2 - IS 5182 (Part 2): 2001 (RA 2017) BDL (<3.0)

NO2 - IS 5182 (Part 6): 2006 (RA 2017) BDL ((<5.0)

Lead - IS 5182 (Part 22): 2004 (RA 2014)

BDL - Below Detectable Limit.

Analyzed By J.M. Thippeswamy

Authorized St K Ramakris W Technical

becognized by Government of Karnataka, Maharashtra, Gox for DGPS survey

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is acither inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles 7 Days and ILC samples from the date of issue of Month test certificate unless otherwise
- This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing
- Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only

Approved by NABL & Recognized by Ministry of Environment, Forest and Climate Change for Laboratory





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3 nd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Ballaev (Kamataka) Ph : +91 8394 229433 & 295018 : gems hpt@val.oo.com. e-mail

Website : www.globalmining.in

GEMS-LD/TF/11/01 Date: 09.03.2020

TEST REPORT OF AMBIENT NOISE LEVEL MONITORING

'Granite Building Stone Quarry of

Shri, Jovin George'

Name of the Customer/Address Extent: 4.5180 Ha. (11.1639Acres)

Sy. Nos: 275/1A, Tripangottur Village,

Thalassery Taluk, Kannur District, Kerala State.

Sample Description : Ambient Noise Level monitoring

3 Sample Collected By GLOBAL Environment & Mining Services

Particulars of Sample Collected Noise Level Meter (Equinox-107)

5 Duration of the Monitoring 24 Hours Sampling

Date of Analysis Completion : 09.03.2020

Report No : ULR-TC532320000000103F

Result

Date	04.03.2020	05.03.2020	
Name of the Location	Core Zone	Buffer zone	
Time (hrs)	N1	N2	
6.00	35.7	41.4	
7.00	38.3	42.5	
8.00	42.5	45.7	
9.00	49.8	46.4	
10.00	54.8	49.2	
11.00	53.7	50.2	
12.00	51.8	47.2	
13.00	52.6	51.1	
14.00	53.4	49.7	
15.00	49.2	50.1	
16.00	50.8	48.7	
17.00	51.7	49.2	
18.00	50.8	47.2	
19.00	49.8	48.8	
20.00	43.8	49.5	
21.00	36.0	46.2	
22.00	34.0	47.4	
23.00	36.6	38.4	
00.00	35.0	37.0	
01.00	36.2	36.0	
02.00	36.0	38.3	
03.00	35.2	37.5	
04.00	35.6	37.6	
05.00	37.8	38.7	

- Approved by NABL & Recognized by Ministry of Environment, Forest and Climate Change for Laboratory Recognized by Government of Kannataka, Maharashira, Goa for DGPS survey

- The result listed refers only to the tested samples & applicable perameters. Endorsement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days. Minarals 3 Months. Filter papers & Thimbles 7 Days and ILC samples from the date of issue of Month test certificate unless otherwise
- This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.
- Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosepete jurisdiction only





(Consulting Engineers, Mine designers, Gordonist & Surveyors)

3 rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Kamataka) Ph : +91 8394 229433 & 295018

gems hpt@yahoo.com. e-mail Website : www.globalmining.in

	ULR	ULR-TC5323200000001031		
L max	54.8	51.1		
L min	34.0	36.0		
Ld	50.8	48.4		
Ln	35.9	41.8		
Ldn	49.5	50.1		

on recogging and	Category of Area	Limit in dB(A) Leq		
Area Code		Day Time	Nighttime	
A	Industrial Area	75 *	70	
В	Commercial Area	65	55	
C	Residential Area	55	45	
D	Silence Area	50	40	

Day time shall mean from 6:00 am and 10.00 pm

Night time shall mean from in between 10,00 pm and 5,00 am

Silence zone is an area comprising not less than 100 meters around hospitals, educational institutions, courts, religious places or any other area which is declared as such by the competent authority

Mixed categories of areas may be declared as one of the four above mentioned categories by the competent authority Note

*dB(A) Leq denotes the time weighted average of the level of sound in decibels on scale A which relatable to human being

A "decibel" is a unit in which noise is measured

"A", in dB(A) Leq, denotes the frequency weighting in the measurement of noise and corresponds to frequency response characteristics of the human ear.

Leq: It is energy mean of the noise level over a specified period.



- Approved by NABL & Recognized by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognized by Government of Karnataka, Maharashtra, Goa for DGPS survey

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days. Minerals 3 Months, Filter papers & Thimbles 7 Days and ILC samples from the date of issue of Month test certificate unless otherwise
- This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing
- Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3 nd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Kamataka) -+91 8394 229433 & 295018

e-mail : gems hpt@yahoo.com, Website : www.globalmining.in

> EMS-LD/TF/11/01 Date: 09.03.2020

ANALYSIS REPORT OF WATER QUALITY DATA

'Granite Building Stone Quarry of

Shri, Jovin George'

Name of the Customer/Address : Extent: 4.5180 Ha. (11.1639Acres)

Sy. Nos: 275/1A, Tripangottur Village,

Thalassery Taluk, Kannur District, Kerala State. : GLOBAL Environment & Mining Services

Sample Collected By

Sampling Method

Date of sample collection 5 Date of sample Received Date of sample Analyzed

Report Number

Grab Sample 05.03.2020 08.03.2020

09.03.2020

ULR-TC532320000000104F

Result

SI.	Parameters	ameters Unit	Result	Test Protocol	Requirement/Limit IS: 10500: 2012		
110.					Acceptable	Permissible	
1	Hq	.*.	7,1	APHA 22th Edition 2012 4500 B (Pg No. 4-92 to 4-96)	6.5	8.5	
2.	Colour*	Hazen	<5	IS: 3025 (PART 14)- 1984, RA-2012 Platinum cobalt Method	5	15	
3.	Taste*		Ag	IS 3025 Part 8 1984	Ag	Ag	
4	Odour*	-	Ag	IS: 3025 (Part 5) = 1983, Ra-2012, True Octour	Ag	Ag	
5.	Turbidity	NTU	0.31	APHA 22 nd Edition 2012 2130 B (Pg No. 2-14)	1	5	
6	Conductivity	μS/cm	191	APHA 22 rd Edition 2012 2510 B (Pg No. 2-54)	4	-	
7.	Total Dissolved Solids	mg/L	158	APHÃ 22 nd Edition 2012 2540 B * (Pg No. 2-65)	500	2000	
8.	Total Alkalinity as CaCO ₅	mg/L	51	- APHA 22 ^{nl} Edition 2320 B (Pg No. 2-35)	200	600	
9.	Total Hardness as CaCOs	mg/L	142	- APHA 22 rd Edition 2012 2340 C (Pg No. 2-46)	200	600	
10.	Calcium as Ca	mg/L	17	 APHA 22nd Edition 2012 3500 Ca B (Pg No. 3-84) 	75	200	
II.	Magnesium as Mg	mg/L	8.1	APHA 22 rd Edition 2012 3500 B-Mg By Calculation	30	100	
12.	Chloride as Cl	mg/L	21.2	APHA 22 ^{nl} Edition 2012 4500 Cl (Pg No. 4-72)	250	1000	
13.	Sulphate as SO ₄	mg/L	91	APHA 22 nd Edition 2012 4500 SO42 – E (Pg No. 4-190)	200	400	
14.	Nitrates as NOs	mg/L	3.20	APEA 23 rd Edition = 4500 NO ₃ , = E (Pg No. 4-131 to 4-132)	45	NR	
14.	Nitrate Nitrogen as NOs	mg/L	14	APHA 22 rd Edition 2012 4500 NO3 E (Pg No. 4-125 to 4-127)	45	No relaxation	

- Approved by NABL & Recognized by Ministry of Environment, Forest and Climate Change for Laboratory Recognized by Government of Kamatuka, Muharashtra, Goa for DGPS survey

- The result listed refers only to the tested samples & applicable parameters. Endousement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles 7 Days and ILC samples from the date of issue of Month test certificate unless otherwise.
- This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media willout special permission in writing
- Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3 Main Road, Basaveswara Badavane, HOSPET - 583201, Dist., Bellary (Kamataka)

: +91 8394 229433 & 295018 Ph gems hpt@yahoo.com, e-mail Website : www.globalmining.in

					ULR-TC532320000000104F		
15.	Fluoride as F	mg/L	0.82	APHA 23rd Edition 2017 4500 F-D (Pg No. 4-90 to 4-91)	1.0	1.5	
16.	Iron as Fe	mg/L	0.42	APHA 23 ^{sd} Edition – 3500 Fe-B (Pg No. 3-80 to 3-82)	0.3	NR	
17.	Sodium as Na	mg/L	7.45	APHA 23 rd Edition 2017 Na 3500 B (Pg No. 3-99 to 3-100)		849	
18.	Potassium as K	mg/L	0.62	APHA 23 nd Edition 3500 K B (Pg No. 3-89 to 3-90)		4	
19.	BOD 3 doys at 27° C	mg/L	NIL	IS:3025 (P.44) - 1993 , RA-2014,		165	
20.	COD as O2	mg/L	NIL	APHA 23 nd Edition 5220 C (Pg No. 5-18 to 5-19)		548	
21.	Oil & Grease	mg/L	NIL	APHA 23 rd Edition 5520 B (Pg No.5-41 to 5-42)	0.5	NR	
22.	Cadmium as Cd*	mg/L	< 0.001	APHA 23 RD Edition-3111 –B (Pg No.3-20 to 3-21)	0.003	NR	
23.	Copper as Cu	mg/L	<0.001	APHA-23 RD Edition 3111-B (Pg No.3-20 to 3-21)	0.02	1.5	
14.	Nickel as Ni	mg/L	< 0.001	APHA-23 ⁸⁰⁵ Edition-3111 -B (Pg No. 3-20 to 3-21)	0.02	NR	
25.	Zinc as Zn	mg/L	<0.1	APHA-23 RD Edition-3111-B (Pg No. 3-20 to 3-21)	5	15	
6.	Salinity*	PPT	NIL	APHA-23 RD Edition-3111-B (Pg No. 3-20 to 3-21)			
7.	Total Phosphereus	mg/L	<0.01	APEIA-23 RD Edition 4500-D (Pg No. 4-154)		*	
18.	Total Coliforms*	MPN/ 100ml	Ab	APHA 22 nd Edition 9222 B (Pg No.9-78)		2 2	
19,	Feacal Coliforns	MPN/ 100ml	Ab	APEIA 22 ^{nl} Edition 9222 D (Pg No.9-85)		¥	
0.	Phyto Plankton*	Unit/L	Ab	APHA 23 rd Edition 10200 F (Pg No.10-17)			

Note: BDL Below Detectable Limit Ag: Agreeable

NR: No Relaxation RA: reaffirmed Ab: Absent -

End of report

Analyzed By Chemist



Approved by NABL & Recognized by Ministry of Environment, Forest and Climate Change for Laboratory Recognized by Government of Karnataka, Maharashtra, Goa for DGPS survey

Note:

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied Water Samples will be destroyed after 15Days. Minerals 3 Months, Filter papers & Thimbies 7 Days and ILC samples from the date of issue of Month test certificate unless otherwise specified.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.

Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only